


PANEL NAME:				IP ADDRESS:		N/A			
MOUNTING LOCATION:				SUBNET MASK:		N/A			
TRANSFORMER FEED:				DEFAULT GATEWAY:		N/A			
PANEL TYPE:		NXL-D16a		PANEL DIMENSIONS:		24.00"H x 20.00"W x 6.00"D			
LEFT SIDE				RIGHT SIDE					
LOAD DESCRIPTION	SOURCE	ADDRESS	DEVICE	DEVICE	ADDRESS	SOURCE	LOAD DESCRIPTION		
CRC2180 RELAY CONTROLLER				CRC7000	-1				
				CRC7000	-2				
CRC2180 RELAY CONTROLLER				CRC7000	-3				
				CRC7000	-4				
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-1			
	CHANNEL 2		-2		CRC7000	-2			
	CHANNEL 3		-3		CRC7000	-3			
	CHANNEL 4		-4		CRC7000	-4			
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-3			
	CHANNEL 2		-2		CRC7000	-4			
	CHANNEL 3		-3		CRC7000	-1			
	CHANNEL 4		-4		CRC7000	-2			
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-1			
	CHANNEL 2		-2		CRC7000	-2			
	CHANNEL 3		-3		CRC7000	-3			
	CHANNEL 4		-4		CRC7000	-4			
	CHANNEL 1		-1	CRC4214 0-10 DIMMER	CRC7000	-3			
	CHANNEL 2		-2		CRC7000	-4			
	CHANNEL 3		-3		CRC7000	-1			
	CHANNEL 4		-4		CRC7000	-2			
CRC6001 (AMP) SPACE FOR AMPLIFIER				CRC7000	-1				
				CRC7000	-2				
				CRC7000	-3				
				CRC7000	-4				
				SPACE					

INSTALLING CONTRACTOR TO USE: 16 AWG, BELDEN 6200 UE OR EQUAL; REFERENCE 2-WIRE DATA BUS WIRING DETAIL