


PANEL NAME:				IP ADDRESS:		N/A			
MOUNTING LOCATION:				SUBNET MASK:		N/A			
TRANSFORMER FEED:				DEFAULT GATEWAY:		N/A			
PANEL TYPE:		NXL-D24a		PANEL DIMENSIONS:		30.00"H x 24.00"W x 6.00"D			
LEFT SIDE				RIGHT SIDE					
LOAD DESCRIPTION	SOURCE	ADDRESS	DEVICE	DEVICE	ADDRESS	SOURCE	LOAD DESCRIPTION		
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
		-1	CRC7000	CRC7000	-2				
		-3	CRC7000	CRC7000	-4				
	CHANNEL 1		-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER		-4	CHANNEL 4	
	CHANNEL 2		-2				-3	CHANNEL 3	
	CHANNEL 3		-3				-2	CHANNEL 2	
	CHANNEL 4		-4				-1	CHANNEL 1	
	CHANNEL 1		-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER		-4	CHANNEL 4	
	CHANNEL 2		-2				-3	CHANNEL 3	
	CHANNEL 3		-3				-2	CHANNEL 2	
	CHANNEL 4		-4				-1	CHANNEL 1	
	CHANNEL 1		-1	CRC4214 0-10V DIMMER	CRC4214 0-10V DIMMER		-4	CHANNEL 4	
	CHANNEL 2		-2				-3	CHANNEL 3	
	CHANNEL 3		-3				-2	CHANNEL 2	
	CHANNEL 4		-4				-1	CHANNEL 1	
SPACE				SPACE					
SPACE				SPACE					
INSTALLING CONTRACTOR TO USE: 16 AWG, BELDEN 6200 UE OR EQUAL; REFERENCE 2-WIRE DATA BUS WIRING DETAIL									